

dedicated chartering management

TOMINI UNITY - DESCRIPTION

NAME:	TOMINI UNITY	
TYPE:	BULK CARRIER	
IMO NO.:	9718167	
BUILT:	JANUARY 2017 AT CHINA SHIPPING INDUSTRY (JIANGSU) CO LTD	
PORT OF REGISTRY:	MAJURO, MARSHALL ISLANDS	
CLASS:	LLOYD'S REGISTER 100 A1	
TECHNICAL MANAGER:	TOMINI TRANSPORTS LLC, DUBAI	
COMMERCIAL MANAGER:	ALPINA CHARTERING, DENMARK	
DWAT / DRAFT / DISPLACEMEN	IT:	
SUMMER SALT WATER:	63,590.00 MT / 13.300 M / 75,226.00 MT	
TROPICAL:	65,322.00 MT / 13.577 M / 76,958.00 MT	
WINTER:	61,861.00 MT / 13.023 M / 73,497.00 MT	
FRESH WATER:	63,590.00 MT / 13.601 M / 75,226.00 MT	
LIGHT SHIP:	11,636.60 MT	
TPC AT SUMMER DRAFT:	62.38 MT/CM	
GROSS TONNAGE:	36,415.00	
NETT TONNAGE:	21,573.00	
SUEZ GROSS / NETT:	37,662.66 / 33,687.88	
PANAMA TONNAGE:	30,213.00	
LOA:	199.90 M / 655.84 FT	
BEAM:	32.26 M / 105.84 FT	
CARGO HOLDS / CAPACITY HOLDS/HATCHES: DIMENSIONS: GRAIN CAPACITY: BALE CAPACITY:	5 / 5 NO. 1: 19.68 M X 18.26 M NO. 2-5: 22.96 M X 18.26 M NO. 1: 13,921.70 CBM / 491,640.196 CBFT NO. 2: 17,660.70 CBM / 623,681.735 CBFT NO. 3: 15,301.60 CBM / 540,370.904 CBFT NO. 4: 15,815.10 CBM / 558,504.986 CBFT NO. 5: 15,943.30 CBM / 563,032.326 CBFT TOTAL: 78,642.40 CBM / 2,777,230.145 CBFT NO. 1: 13,200.00 CBM / 466,153.600 CBFT	
	NO. 2: 16,650.00 CBM / 587,989.200 CBFT NO. 3: 14,080.00 CBM / 497,230.510 CBFT NO. 4: 15,000.00 CBM / 529,720.000 CBFT NO. 5: 14,750.00 CBM / 520,891.330 CBFT TOTAL: 73,680.00 CBM / 2,601,984.640 CBFT	
CO2 FITTED:	YES, IN ALL HOLDS	

www.alpina.dk

VENTILATION IN HOLDS:	YES, NATURAL (4 VENTS EACH HOLD)		
STRENGTHEN FOR HEAVY CARGOES:			
	YES, STRENGTH	YES, STRENGTHENED FOR HEAVY CARGOES	
	HOLDS NO 2, 4 MAY BE EMPTY		
	HOLD NO 3 MA		
	TANK TOP:	HOLDS 2, 4: 20 MTS/M2	
		HOLDS 1, 3, 5: 25 MTS/M2	
	UPPER DECK:	STATE DECK: 3.5 MTS/M2 HATCH COVERS:1.4 MTS/M2	
DANGEROUS CARGOES:	YES		
CRANES:	4 REVOLVING	CRANES	
	30 MT SWL AT		
GRABS:	4 WIRELESS RA	ADIO REMOTE CONTROLLED 12 CBM GRABS	
SPEED / CONSUMPTION:	LADEN:	ABT 11.75 KN / ABT 22.52 MT/DAY IFO + 0.1 MT/DAY MDO	
		ABT 12.75 KN / ABT 27.95 MT/DAY IFO + 0.1 MT/DAY MDO	
	BALLAST:	(LIGHT BALLAST, WITHOUT FLOODING OF HOLD 3):	
		ABT 12.25 KN / ABT 20.81 MT/DAY IFO + 0.1 MT/DAY MDO	
		ABT 13.25 KN / ABT 23.14 MT/DAY IFO + 0.1 MT/DAY MDO	
	IDLE:	ABT 2.3 MT/DAY IFO + 0.1 MT/DAY MDO	
	WORKING:	ABT 5.3 MT/DAY IFO + 0.1 MT/DAY MDO	
	BOILER:	ABT 1.0 MT/DAY (IN PORT/ANCHORAGE)	
	THE VESSEL CONSUMES ABT 2.0 MT/DAY FOR BALLASTING/DEBALLASTING		
	IFO GRADE:	RMG 380 AS PER ISO 8217:2010	
	MDO GRADE:	ISO 8217:2010 DMA OR DMB	
	MARINE FUELS ALWAYS TO BE SUPPLIED IN ACCORDANCE WITH THE ISO 8217:2010		
	SPECIFICATIONS AND MARPOL ANNEX VI		
	THE VESSEL IS CAPABLE OF MAINTAINING AN AVERAGE SPEED AND AN AVERAGE		
	DAILY CONSUMPTION AS ABOVE, EXCLUDED BUNKERS CONSUMED FOR BALLASTING/DEBALLASTING AND EXCHANGE OF BALLAST, FLOODING HOLD 3, HOLD CLEANING, BILGE PUMPING, BOILER, ALWAYS IN GOOD WEATHER		
		MEANING UPTO AND INCLUDING BEAUFORT SCALE 4, DOUGLAS SEA	
	STATE 3, NO ADVERSE CURRENT/NEGATING EFFECT OF FAVORABLE CURRENT, PROVIDED NO FOULING DUE THE VESSELS STAYING FOR 20 DAYS OR MORE IN A		
	THE SPEED/CONSUMPTION WARRANTY IS ONLY APPLICABLE FOR SEA PASSAGES LONGER THAN 48 HRS CONSECUTIVE SAILING AND 24 HRS AFTER COMMENCING SEA PASSAGE TO 24 HRS PRIOR END OF SEA PASSAGE. THE SPEED/CONSUMPTION		
		DES NOT INCLUDE NAVIGATION IN CANALS, TRANSITTING HRA (HIGH	
	RISK AREAS) AI	ND TSS (TRAFIC SEPARATION SCHEMES),	
	NARROW/RESTRICTED/TIDAL/ICE AFFECTED WATERS, SAILING WITH PILOT ONBOARD,		
		ILITY, WHEN THE SPEED IS REDUCED DUE TO CHARTERERS'	
		S OR FOR REASONS OF SAFETY OR WHEN ENTERING/EXITING SECA/ECA. USTIFIED SPEED CLAIM (UNDER PERFORMANCE), THERE SHALL BE AN	
		OR FUEL UNDER-CONSUMPTION AND IN CASE OF A JUSTIFIED	
		N CLAIM THERE SHALL BE A COMPENSATION FOR TIME SAVED IN CASE	
	OF OVER PERF		

www.alpina.dk

THE VESSEL MAY BURN MDO WHEN MANOEUVRING, IN NARROW WATERS, CANALS, RESTRICTED AREAS, RIVERS, WHEN ENTERING/LEAVING PORTS. AS PER RECOMMENDATIONS OF BMP4 VESSELS FIRE AND BALLAST PUMPS WILL BE KEPT ON STANDBY AND ACCORDINGLY VESSEL WILL BE RUNNING ADDITIONAL AUXILLIARY ENGINE/S AND THUS ALLOWED TO CONSUME BUNKERS AS DESCRIBED FOR BALLASTING/DEBALLASTING WHENEVER TRANSITTING ANY HRA AREAS

ALL SPEED/CONSUMPTION FIGURES ARE "ABOUT" AND GIVEN IN GOOD FAITH, "ABOUT" MEANS +/- 0.5 KNOTS FOR SPEED AND +/- 5% FOR CONSUMPTION.

ALL DETAILS "ABOUT" GIVEN IN GOOD FAITH BUT WITHOUT GUARANTEE.