

dedicated chartering management

## **TOMINI GHIBLI - DESCRIPTION**

NAME:	TOMINI GHIBLI (EX SEA ANGEL)		
TYPE:	BULK CARRIER		
IMO NO.:	9723942		
BUILT:	2016 AVIC WEIHAI CO. LTD. CHINA		
PORT OF REGISTRY:	MAJURO, MARSHALL ISLANDS		
CLASS:	ABS		
TECHNICAL MANAGER:	TOMINI TRANSPORTS LLC, DUBAI		
COMMERCIAL MANAGER:	ALPINA CHARTERING, DENMARK		
DWAT / DRAFT / DISPLACEMEN	NT:		
SUMMER SALT WATER:	37,896.30 MT / 10.621 M / 46,718.80 MT		
TROPICAL:	38,995.70 MT / 10.842 M / 47,818.20 MT		
WINTER:	36,799.20 MT / 10.400 M / 45,621.80 MT		
FRESH WATER:	37,897.50 MT / 10.856 M / 46,720.00 MT		
TROPICAL FRESH WATER:	38,972.40 MT / 11.077 M / 47,794.90 MT		
LIGHT SHIP:	8,822.537 MT		
TPC AT SUMMER DRAFT:	49.70 MT/CM		
GROSS TONNAGE:	23,741.00		
NETT TONNAGE:	13,302.00		
SUEZ GROSS / NETT:	25,057.97 / 22,123.12		
PANAMA TONNAGE:	19,770.00		
LOA:	181.00 M / 593.83 FT		
BEAM:	30.00 M / 98.43 FT		
CARGO HOLDS / CAPACITY			
HOLDS/HATCHES: HATCH DIMENSIONS:	5 / 5 NO. 1: 16.80 M X 15.00 M NO. 2-5: 19.20 M X 19.20 M		
GRAIN CAPACITY:	NO. 1: 8,670.868 CBM / 306,211.704 CBFT NO. 2: 10,315.985 CBM / 364,309.011 CBFT NO. 3: 10,331.606 CBM / 364,860.666 CBFT NO. 4: 10,331.606 CBM / 364,860.666 CBFT NO. 5: 10,546.115 CBM / 372,436.052 CBFT TOTAL: 50,196.180 CBM / 1,772,678.099 CBFT		
BALE CAPACITY:	NO. 1: 8,313.810 CBM / 293,602.201 CBFT NO. 2: 9,928.154 CBM / 350,612.759 CBFT NO. 3: 9,938.262 CBM / 350,969.723 CBFT NO. 4: 9,938.262 CBM / 350,969.723 CBFT NO. 5: 10,205.746 CBM / 360,415.920 CBFT TOTAL: 48,324.234 CBM / 1,706,570.326 CBFT		

www.alpina.dk

CO2 FITTED:	YES, IN ALL HOLDS		
VENTILATION IN HOLDS:	YES, MECHANICAL/ELECTRICAL		
A60:	YES		
STRENGTHENED FOR HEAVY C		ED FOR HEAVY CARGOES AY BE EMPTY	
		DLDS 1-5: 21 MTS/M2 /DRAULIC FOLDING TYPE HATCHES(MAKER IS TTS HUATAI). NO DECK O ON TOP OF HATCH COVERS ALLOWED.	
CRANES: GRABS:	4 REVOLVING CRANES (TTS MARINE CARGO CRANE) 30.00 MT SWL AT 25 M RADIUS N/A – VESSEL IS NOT GRABS FITTED		
SPEED / CONSUMPTION:	AB BALLAST: (LI AB AB IDLE: AB WORKING: AB THE VESSEL IS USIN VLSFO GRADE: ISO LSMGO GRADE: ISO LSMGO GRADE: ISO MARINE FUELS ALM SPECIFICATIONS AD THE VESSEL IS CAP DAILY CONSUMPTI BALLASTING/DEBA CLEANING, BILGE F CONDITIONS, MEA	AT 12.0 KN / ABT 18.00 MT/DAY VLSFO AT 13.5 KN / ABT 23.00 MT/DAY VLSFO IGHT BALLAST, WITHOUT FLOODING OF HOLD 3): AT 12 KN / ABT 16.00 MT/DAY VLSFO AT 13.5 KN / ABT 21.00 MT/DAY VLSFO AT 13.5 KN / ABT 21.00 MT/DAY VLSFO AT 2.5 MT/DAY VLSFO + 0.2 MT/DAY LSMGO AT 5.3 MT/DAY VLSFO + 0.2 MT/DAY LSMGO NG ABT 2.0 MTS FOR BALLASTING/DEBALLASTING A 2217:2010 CATEGORY ISO-F-RMG 380 D 8217:2010 CATEGORY ISO-F-DMA/DMB WAYS TO BE SUPPLIED IN ACCORDANCE WITH THE ISO 8217:2010 ND MARPOL ANNEX VI ABLE OF MAINTAINING AN AVERAGE SPEED AND AN AVERAGE ION AS ABOVE, EXCLUDED BUNKERS CONSUMED FOR ALLASTING AND EXCHANGE OF BALLAST, FLOODING HOLD 3, HOLD PUMPING, BOILER, ALWAYS IN GOOD WEATHER ANING UPTO AND INCLUDING BEAUFORT SCALE 4, DOUGLAS SEA RSE CURRENT/NEGATING EFFECT OF FAVORABLE CURRENT, JLING DUE THE VESSELS STAYING FOR 20 DAYS OR MORE IN A AGE(S).	
	THE SPEED/CONSUMPTION WARRANTY IS ONLY APPLICABLE FOR SEA PASSAGES LONGER THAN 48 HRS CONSECUTIVE SAILING AND 24 HRS AFTER COMMENCING SEA PASSAGE TO 24 HRS PRIOR END OF SEA PASSAGE. THE SPEED/CONSUMPTION WARRANTY DOES NOT INCLUDE NAVIGATION IN CANALS, TRANSITTING HRA (HIGH RISK AREAS) AND TSS (TRAFIC SEPARATION SCHEMES), NARROW/RESTRICTED/TIDAL/ICE AFFECTED WATERS, SAILING WITH PILOT ONBOARD, IN POOR VISIBILITY, WHEN THE SPEED IS REDUCED DUE TO CHARTERERS' INSTRUCTIONS OR FOR REASONS OF SAFETY OR WHEN ENTERING/EXITING SECA/ECA. IN CASE OF A JUSTIFIED SPEED CLAIM (UNDER PERFORMANCE), THERE SHALL BE AN ALLOWANCE FOR FUEL UNDER-CONSUMPTION AND IN CASE OF A JUSTIFIED		

www.alpina.dk

CONSUMPTION CLAIM THERE SHALL BE A COMPENSATION FOR TIME SAVED IN CASE OF OVER PERFORMANCE.

THE VESSEL MAY BURN MDO WHEN MANOEUVRING, IN NARROW WATERS, CANALS, RESTRICTED AREAS, RIVERS, WHEN ENTERING/LEAVING PORTS. AS PER RECOMMENDATIONS OF BMP5 VESSELS FIRE AND BALLAST PUMPS WILL BE KEPT ON STANDBY AND ACCORDINGLY VESSEL WILL BE RUNNING ADDITIONAL AUXILLIARY ENGINE/S AND THUS ALLOWED TO CONSUME BUNKERS AS DESCRIBED FOR BALLASTING/DEBALLASTING WHENEVER TRANSITTING ANY HRA AREAS

ALL SPEED/CONSUMPTION FIGURES ARE "ABOUT" AND GIVEN IN GOOD FAITH, "ABOUT" MEANS +/- 0.5 KNOTS FOR SPEED AND +/- 5% FOR CONSUMPTION.

ALL DETAILS "ABOUT" GIVEN IN GOOD FAITH BUT WITHOUT GUARANTEE.