

TOMINI NOBILITY - DESCRIPTION

NAME: TOMINI NOBILITY
TYPE: BULK CARRIER
IMO NO.: 9842827
BUILT: 2020 AT TAIZHOU KOUAN SHIPBUILDING CO. LTD.
PORT OF REGISTRY: MAJURO, MARSHALL ISLANDS
CLASS: DNV-GL

TECHNICAL MANAGER: TOMINI TRANSPORTS LLC, DUBAI
COMMERCIAL MANAGER: ALPINA CHARTERING, DENMARK

DWAT / DRAFT:
SUMMER SALT WATER: ABT 81,093 MT / 14.45 M
TROPICAL: ABT 83,253 MT / 14.751M
FRESH WATER: ABT 81,093 MT / 14.781M
LIGHT SHIP: ABT 13,703 MT

TPC AT SUMMER DRAFT: ABT 71.70 MT/CM

GROSS TONNAGE: 44,015
NETT TONNAGE: 27,331
SUEZ GROSS / NETT: 45,789.95 / 42,053.37
PANAMA TONNAGE: 36,788

NEW PANAMA LOCKS FITTED : YES

LOA: 229,00 M
BEAM: 32.26 M
LBP: 225.50 M

CARGO HOLDS / CAPACITY

HOLDS/HATCHES: 7 / 7
DIMENSIONS:
No.1 : 14.705 m X 12.800 m
No.2 : 17.300 m X 15.000 m
No.3 : 17.300 m X 15.000 m
No.4 : 15.570 m X 15.000 m
No.5 : 17.300 m X 15.000 m
No.6 : 17.300 m X 15.000 m
No.7 : 17.300 m X 15.000 m

GRAIN/BALE CAPACITY:
No.1 : 12,466.8 cbm / 12,257.8 cbm
No.2 : 14,898.9 cbm / 14,571.6 cbm
No.3 : 14,450.8 cbm / 14,123.5 cbm
No.4 : 12,814.5 cbm / 12,520.0 cbm
No.5 : 13,916.9 cbm / 13,589.6 cbm
No.6 : 13,889.4 cbm / 13,562.1 cbm
No.7 : 14,275.5 cbm / 13,498.2 cbm
TTL : 96,712.8 cbm / 94,572.8 cbm

CO2 FITTED: NO

VENTILATION IN HOLDS: YES, NATURAL

SPEED / CONSUMPTION:

LADEN:	ABT 12.5 KN / ABT 26.50 MT/DAY IFO + 0.2 MT/DAY MDO ABT 13.0 KN / ABT 29.50 MT/DAY IFO + 0.2 MT/DAY MDO ABT 13.5 KN / ABT 33.00 MT/DAY IFO + 0.2 MT/DAY MDO
BALLAST:	(LIGHT BALLAST, WITHOUT FLOODING OF HOLD (S)): ABT 12.5 KN / ABT 19.50 MT/DAY IFO + 0.2 MT/DAY MDO ABT 14.5 KN / ABT 29.50 MT/DAY IFO + 0.2 MT/DAY MDO
IDLE:	ABT 4.0 MT/DAY IFO + 0.2 MT/DAY MDO
WORKING:	ABT 5.5 MT/DAY IFO + 0.2 MT/DAY MDO
BOILER:	ABT 1.0 MT/DAY (IN PORT/ANCHORAGE)

THE VESSEL IS USING ABT 2.5 MT/DAY FOR BALLASTING/DEBALLASTING

IFO GRADE: RMG 380 AS PER ISO 8217:2010
MDO GRADE: ISO 8217:2010 DMA OR DMB
MARINE FUELS ALWAYS TO BE SUPPLIED IN ACCORDANCE WITH THE ISO 8217:2010 SPECIFICATIONS AND MARPOL ANNEX VI

THE VESSEL IS CAPABLE OF MAINTAINING AN AVERAGE SPEED AND AN AVERAGE DAILY CONSUMPTION AS ABOVE, EXCLUDED BUNKERS CONSUMED FOR BALLASTING/DEBALLASTING AND EXCHANGE OF BALLAST, FLOODING HOLD 3, HOLD CLEANING, BILGE PUMPING, BOILER, ALWAYS IN GOOD WEATHER CONDITIONS, MEANING UPTO AND INCLUDING BEAUFORT SCALE 4, DOUGLAS SEA STATE 3, NO ADVERSE CURRENT/NEGATING EFFECT OF FAVORABLE CURRENT, PROVIDED NO FOULING DUE THE VESSELS STAYING FOR 20 DAYS OR MORE IN A PORT(S)/ANCHORAGE(S).

THE SPEED/CONSUMPTION WARRANTY IS ONLY APPLICABLE FOR SEA PASSAGES LONGER THAN 48 HRS CONSECUTIVE SAILING AND 24 HRS AFTER COMMENCING SEA PASSAGE TO 24 HRS PRIOR END OF SEA PASSAGE. THE SPEED/CONSUMPTION WARRANTY DOES NOT INCLUDE NAVIGATION IN CANALS, TRANSITTING HRA (HIGH RISK AREAS) AND TSS (TRAFFIC SEPARATION SCHEMES), NARROW/RESTRICTED/TIDAL/ICE AFFECTED WATERS, SAILING WITH PILOT ONBOARD, IN POOR VISIBILITY, WHEN THE SPEED IS REDUCED DUE TO CHARTERERS' INSTRUCTIONS OR FOR REASONS OF SAFETY OR WHEN ENTERING/EXITING SECA/ECA. IN CASE OF A JUSTIFIED SPEED CLAIM (UNDER PERFORMANCE), THERE SHALL BE AN ALLOWANCE FOR FUEL UNDER-CONSUMPTION AND IN CASE OF A JUSTIFIED CONSUMPTION CLAIM THERE SHALL BE A COMPENSATION FOR TIME SAVED IN CASE OF OVER PERFORMANCE.

THE VESSEL MAY BURN MDO WHEN MANOEUVRING, IN NARROW WATERS, CANALS, RESTRICTED AREAS, RIVERS, WHEN ENTERING/LEAVING PORTS. AS PER RECOMMENDATIONS OF BMP4 VESSELS FIRE AND BALLAST PUMPS WILL BE KEPT ON STANDBY AND ACCORDINGLY VESSEL WILL BE RUNNING ADDITIONAL AUXILLIARY ENGINE/S AND THUS ALLOWED TO CONSUME BUNKERS AS DESCRIBED FOR BALLASTING/DEBALLASTING WHENEVER TRANSITTING ANY HRA AREAS

ALL SPEED/CONSUMPTION FIGURES ARE "ABOUT" AND GIVEN IN GOOD FAITH, "ABOUT" MEANS +/- 0.5 KNOTS FOR SPEED AND +/- 5% FOR CONSUMPTION.

ALL DETAILS "ABOUT" GIVEN IN GOOD FAITH BUT WITHOUT GUARANTEE.

